

THE STYLE BAKER is a spiral wound gasket specifically developed for usage in hydrofluoric acid and other hazardous chemical applications.

**Temperature Limits**

Cryogenics to 500°F

**Pressure Limits**

The same as pressure rating of ANSI flanges.

**Required Surface Finish**

125 - 250 Microinch Ra

**Sealing Element Tolerances**

Gasket Diameter	Inside Diameter	Outside Diameter	Thickness
Up to 10" 10" to 24"	± 1/64" ± 1/32"	± 1/32" ± 1/16"	± 0.005" ± 0.005"

**Size Range**

All standard ANSI flange size range

**Technical Benefits**

- Prevents hydrofluoric acid attaching the bolts in case of minor leaks
- Early detection of minor leaks
- Containment of HF emissions
- Improves maintenance
- Requires no modification to the flanges

**Design Information**

ASME Constants	
m y	3 10,000 psi

This Data Sheet relates to the material as supplied. The information contained herein is given in good faith, but no liability will be accepted by the Company in relation to same. The acquisition of additional information may necessitate revisions to parts or all of this Data Sheet, and such information will be supplied as it becomes available.

As the Company's products are used for a multiplicity of purposes, and as the Company has no control over the method of their application or use, the Company excludes all conditions or warranties, express or implied, by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the Company and the Customer is given for the Customer's assistance only and without liability on the part of the Company.